



INTERNAL LEAKAGE	EXTERNAL LEAKAGE	VOLTAGE CLASS	B.I.L.	RATED CURRENT	L	C	T	D	P	H	BOLT SIZE	BOLT CIRCLE	DRAWING NUMBER
23Kv BUSHINGS													
21"	24"	23Kv	110	1200A	24.5"	1.75"	1.25-12NF-2A	Ø4.75"	5.75"	17.25"	1/2-13NC (4)	Ø7.250"	16-F-14731
21"	24"	23Kv	150	2300A	24.5"	1.75"	1.75-12UN-2A	Ø4.75"	5.75"	17.25"	1/2-13NC (4)	Ø7.250"	16-F-14727
21"	24"	23Kv	150	3000A	24.5"	1.75"	2.25-12UN-2A	Ø4.75"	5.75"	17.25"	1/2-13NC (4)	Ø7.250"	16-F-15128
38Kv BUSHINGS													
28"	48"	38Kv	200	600A/800A	27.5"	11"	1.00-14NS-2A	Ø4.75"	5.12"	22.38"	1/2-13NC (6)	Ø7.500"	16-F-14782
28"	48"	38Kv	200	1200A	27.5"	11"	1.25-12NF-2A	Ø4.75"	5.12"	22.38"	1/2-13NC (6)	Ø7.500"	16-F-14728
28"	48"	38Kv	200	1600A	27.5"	11"	1.50-12UN-2A	Ø4.75"	5.12"	22.38"	1/2-13NC (6)	Ø7.500"	16-F-15125
28"	48"	38Kv	200	2000A	27.5"	11"	1.75-12UN-2A	Ø4.75"	5.12"	22.38"	1/2-13NC (6)	Ø7.500"	16-F-14827
28"	48"	38Kv	200	2500A	27.5"	11"	2.00-12UN-2A	Ø4.75"	5.12"	22.38"	1/2-13NC (6)	Ø7.500"	16-F-14735
40"	48"	38Kv	250	3000A	32.5"	10"	2.25-12UN-2A	Ø5.75"	6"	24.5"	5/8-11NC (6)	Ø8.250"	16-F-15120
46Kv BUSHINGS													
40"	48"	46Kv	250	1500A	31"	10"	1.50-12UN-2A	Ø5.75"	6"	24.5"	5/8-11NC (6)	Ø8.250"	16-F-15126
40"	48"	46Kv	250	2000A	31"	10"	1.75-12UN-2A	Ø5.75"	6"	24.5"	5/8-11NC (6)	Ø8.250"	16-F-15121
40"	48"	46Kv	250	2500A	31"	10"	2.00-12UN-2A	Ø5.75"	6"	24.5"	5/8-11NC (6)	Ø8.250"	16-F-15122
40"	48"	46Kv	250	3000A	31"	10"	2.25-12UN-2A	Ø5.75"	6"	24.5"	5/8-11NC (6)	Ø8.250"	16-F-15233